



# EXPERT / FAMILY

Expert II 24
Expert II 52
Expert II 24 LX
Expert II 52 LX
Expert II 52 LX

The Best Choice for Sign Makers

The Expert Family provides sign makers with optimum speed, superior quality, solid reliability, unmatched value at an affordable price and an eye-catching color combination.



## EXPERT/

- 24 in. / 52 in
- Up to 350 gram of cutting force
- Up to 705 mm / 635 mm (27.8 in. / 25 in.) per second cutting speed (at 45 degree direction)
- · 3 m tracking



#### **Enhanced AAS II Contour Cutting System**

Automatic-Aligning System (AAS II) guarantee precise contour cutting by detecting the registration marks on digitally produced images. (Available for Expert II LX



#### Handy grooved cut-off tool

This handy and innovative design allows you to cut off a finished job in a straight line easily reducing the possibility of wasting usable material.



#### **Windows Drivers**

Expert II includes a "one click" Windows driver that allows sign makers to edit signs from CorelDraw and output directly to Expert II.



#### User-friendly interface

It comes with the special VLCD software, providing a simple and intuitive workflow for



#### Rhinestone Application

Expert II handles rhinetsone stencil cutting with ease, people are amazed with its great versatility.



#### Dual-port connectivity



# EXPERT//LX

- 24 in. / 52 in.
- Up to 350 gram of cutting force
- Up to 705 mm / 635 mm (27.8 in. / 25 in.) per second cutting speed (at 45 degree direction)
- 3 m tracking
- Advanced contour cutting system AAS II



## Guaranteed 3 meter tracking

It comes with a stable drum that can guarantee 3 meter tracking to ensure quality outputs and saves you from wasted material and cost.



#### VCM

VCM (Voice Coil Motor) ensure cutting quality. As a result, Expert II can provide sophisticated cutting quality steadily and consistently.



users of all levels



GCC Expert II supports dual-port connectivity with USB and serial ports.







Signs

Advertisement

Stickers

Textile

Mod	del Numb	er	EX II-24	EX II-24LX	EX II-52	EX II-52LX
Opei	Operational Method		Roller -Type			
Max.	Max. Cutting Width		600 mm (23.6 in.) 1320 mm (51.96 in.		(51.96 in.)	
Max.	Max. Cutting Length		50m (164 ft)			
Max.	Max. Media Loading Width		719 mm (28.3 in.)		1470 mm (57.87 in.)	
Min.	Min. Media Loading Width		50 mm (1.97 in.)			
Num	Number of Pinch Rollers		3			
Acce	Acceptable Material Thickness		0.8 mm (0.03 in.)			
Moto	Motor Drive		Stepper			
Cutti	Cutting Force		350 g			
Max.	. Cutting S	peed	Up to 705 mm (at 45 degre		Up to 635 mm / sec (25 ips) (at 45 degree direction)	
Acce	Acceleration		0.7 G			
Offse	Offset		0 ~ 1.0 mm (with an increase of 0.025 mm)			
Mecl	Mechanical Resolution		0.012 mm (0.00049 in.)			
Soft	Software Resolution		0.025 mm (0.00098 in.)			
Dista	Distance Accuracy		± 0.254 mm or ± 0.1% of move, whichever is greater			
Repe	Repeatability		±0.1mm			
Mem	Memory Buffer		500 KByte			
Inter	Interfaces		USB 2.0 (Full speed) & Serial (RS-232C)			
Туре	Type of Command		HP-GL, HP-GL / 2			
Cont	Control Panel		10 Control Keys and 6 LED			
Dian	Diameter of Blade		2.5 mm			
Dime	ension	(HxWxD) mm	233 * 25	55 * 880	1065*16	32*620
		(HxWxD) in	9.1*10	)*34.6	41.93 * 62	.25 * 24.41
Net \	Net Weight		11 kg (	24.3 lb)	53 kg (116.4 lb)	
Stan	ıd		Optio	nal	Standard (The dimension and weight contain the stand)	
Pow	Power Supply		AC 100-240V, 50~60 Hz (auto switching)			
Pow	Power Consumption		65.5 watts			
Envi	Environment Temperature		15° C ~ 30° C / 60° F ~ 86° F (operating)			
Envi	Environment Humidity		25 % ~ 75 % relative humidity (operating)			

- Compatible with Windows 2000 / XP / Vista / 7 / 8 and MAC OS X 10.4-10.7.
- ≋ The specification and data sheet may vary with different materials used. In order to obtain the best output quality, please maintain the machine regularly and properly.
- GCC reserves the right to change the specifications without prior notice.
   The above listed specification values are effective only when operated with media certified by GCC.



### **SHOP ONLINE**

www.NovaRhinestone.com

info@NovaRhinestone.com Tel: 888 - 740 - 6682 Fax: 213 - 612 - 4413



807 Maple Ave, Los Angeles, CA 900

849 W 34th St, Houston, TX 77092